

Ethernet Optical Fiber Extender

NO: MOF7101E



Features

- Provides 1 100 Mbps fiber optic and 1 network port which can transform between network data and fiber optic
- With the single-mode dual optical fiber, up to 20 km transmission distance, SC Port
- Compatible with IEEE 802.3 10 BASE-T, IEEE 802.3u 100 BASE-TX/FX Ethernet standards
- Small Size, support MIT Frame

	Item	Description
Power	Power supply	Power Adapter
	Power voltage	DC12-24V
	Consumption	<5W
Ethernet Port	Ethernet Port	LAN:10/100Mbps
	Transmission Distance	LAN: 0~100m
Fiber Port	Fiber Port	Dual Fiber SC Port
	Bandwidth	155Mbps
	Transmission Distance	20km for Single-mode Fiber;
Network Standard	Compatible with	IEEE802.3 10BASE-T,IEEE802.3u 100BASE-TX/FX
LED Status Indicator	Power	1 (Green)
	Ethernet	Green on RJ45
	Fiber	FED, SD, LINK 3 Green LEDs
Protection	ESD	Contact Discharge 6KV; Air Discharge 8KV
	Lightning Protection	Power: 2KV Signal: 1KV Per: IEC61000-4-5
Environmental	Working temperature	-20℃~55℃
	Storage temperature	-40℃~70℃
	Humidity (non-condensing)	0%~95%
Mechanical	Dimension (L×W×H)	103mm×82mm×25mm
	Material	Aluminum Alloy
	Color	Black
	N.W.	180g
Stability	MTBF	>30000 h

Note: The specifications are subjected to change without prior notice.

Version 1.1

Exclusive Distributor in HK, China and Macau



WELFARE ELECTRONIC COMPONENT LIMITED

OFFICE: 1/F, Cheong Lok Building, 199 Cheung Sha Wan Road, Sham Shui Po, Kowloon, Hong Kong
SHOP: G/F & 1/F, Ming Chu Building, 201 Apliu Street, Sham Shui Po, Kowloon, Hong Kong

(852) 3182 0888
(852) 3182 0808
cs@wecl.com.hk
WECLonline.com